



# Daphne Cleaner A

## High Performance Hydrocarbon Cleaner

### Description

This is a highly purified hydrocarbon cleaner/ degreaser specially developed by IDEMITSU. It is able to meet today's stringent requirement for industrial cleaning & degreasing and being totally environment friendly at the same time for it does not contain O-zone depleting substances.

### Application

Recommended as a cleaner/ degreaser for all types of metals. It is also able to clean rubber and plastic parts.

### Characteristics

1. **Excellent Cleaning/ Degreasing Abilities** - Extremely good for industrial cleaning/ degreasing of all types of metals, plastic and rubber parts.
2. **Extremely Low Odour & Toxicity** - Manufactured from purified organic compound, it does not contained impurities and thus extremely low odour and toxicity. It does not cause dermatitis, thus, promoting pleasant and healthy working environment.
3. **Good Anti-Rust Performance** - Compared with chlorine type solvent (trichloroethylene, 1.1.1. trichloroethane), it has less tendency to absorb moisture from the atmosphere, thus, better anti-rust performance.

### Packing

20L pail, 200L drum

The information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.

## Lubricant Product Information



### Typical Specifications

### Daphne Cleaner A

#### ASTM

#### METHOD

|                                 |        |            |
|---------------------------------|--------|------------|
| Appearance                      | -      | Colourless |
| Colour                          | D-1500 | L0.5       |
| Density 15 °C g/cm <sup>3</sup> | D-4052 | 0.8068     |
| Viscosity, cSt @ 40 °C          | D-445  | 0.914      |
| Flash Point (PM), °C            | D-93   | 51         |

The information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.